

mesa³



DESIGNED &
ASSEMBLED
★ ★ IN ★ ★
USA

ULTRA
RUGGED™

YOUR OFFICE, ANYWHERE.

The Mesa 3 Rugged Tablet offers powerful new functionality, while retaining impressive features from the popular Mesa 2 Rugged Tablet. Its Quadcore Pentium processor is ready to run even the most demanding field data collection application, while its rugged ergonomic design is ready to handle a long day on the job in some of the harshest environments out there. Ready to experience Juniper Rugged?

BUILT JUNIPER RUGGED™

With IP68 and MIL-STD-810G ratings, the Mesa 3 is waterproof, dustproof, and shockproof. Rest assured that rain, extreme temperatures, and dirt won't stop a productive workday.

POWERFUL PROCESSING POWER

Expect lightning-fast speeds all day long with the Mesa 3's Quadcore Intel® Pentium N4200 processor and large memory and storage space. Running a full Windows 10 operating system, this device was made to handle large files and detailed maps.

ALL-DAY USABILITY

From its ergonomic enclosure to its sunlight-readable display down to its 10-hour battery life, the Mesa 3 is made for long days on the job.

CAREFULLY DESIGNED AND SUPPORTED

It's more than a rugged tablet. Designed and assembled in the United States, the Mesa 3 promises device longevity and low failure rates. In addition, each device is supported by live and personalized customer support representative whenever it's needed.



Designed and assembled in the United States, the Mesa 3 Rugged Tablet provides its users with the ultimate data collection experience – wherever the job takes them. From its powerful processor to its all-day battery life to its ultra-rugged design, the Mesa 3 claims best-in-class features for anyone requiring a rugged device for mobile data collection.

PROCESSOR


- Quad-core Intel® Pentium N4200 processor

OPERATING SYSTEM AND SOFTWARE

- Microsoft® Windows 10 (Android models also available)
- Multiple languages supported (English, French, Spanish, German, Portuguese)

MEMORY AND DATA STORAGE

- 8 GB RAM (LPDDR4)
- 128 GB or 256 GB flash storage
- User-accessible MicroSDXC card slot



GRAPHICS

- Intel® HD Graphics

DISPLAY

- Active viewing area: 7" (178 mm)
- Resolution: WXGA (1280 x 800)
- High-visibility backlit LCD for best-in-class sunlight view-ability
- Portrait or landscape orientation with automatic screen rotation

TOUCHSCREEN

- Projected capacitive multi-touch interface for use with gloves, small tip stylus, and in wet conditions
- Optically bonded for increased visibility and strength
- Chemically-strengthened Dragontrail™ High Ion-Exchange (HIE™) cover glass for excellent impact and scratch resistance

KEYPAD

- Adjustable LED backlit keys
- Four-way directional navpad
- Windows/home key
- Power key
- Enter key
- Three user-programmable function keys
- OEM configurable/customizable

PORTS

- USB 3.0 x1
- 3.5 mm audio jack
- 12 VDC power input jack
- Docking connector (Pwr, USB 2.0, HDMI, & ethernet)
- Loud output speaker for noisy environments
- Dual digital microphone input for improved clarity
- Optional RS-232 9-Pin D-Sub connector with 5VDC power output



BATTERY

- Removable Li-Ion battery, 43.2 Whr
- Operates 8–10 hours on one charge
- Removable battery, easily changeable in field
- Optimized for strong performance in cold temperatures
- Excellent lifecycle performance
- Optional internal 21.6 Whr battery provides hot-swap capability and an additional 4–5 hours runtime

PHYSICAL

- Size: 5.40" w x 8.48" l x 1.36" d (137 x 215 x 35 mm)
- Weight: 1.5–2 lbs (680–907 g) depending on battery configuration
- Durable, chemical- and shock-resistant design
- Easy-to-grip, impact-absorbing, overmolded bumpers
- Lightweight and ergonomic design

JUNIPER RUGGED™

- IP68 waterproof and dustproof
- Operating temperature: -4 F to 122 F (-20 C to 50 C)
- Storage temperature: -22 F to 158 F (-30 C to 70 C)
- Shockproof: multiple drops from 4' (1.2–1.5 m) onto concrete
- Designed for MIL-STD-810G test procedures: Method 500.5 Low Pressure (Altitude); Method 501.5 High Temperature; Method 502.5 Low Temperature; Method 503.5 Temperature Shock; Method 506.5 Rain; Method 507.5 Humidity; Method 510.5 Sand and Dust; Method 512.5 Immersion; Method 514.6 Vibration; Method 516.6 Shock

WIRELESS CONNECTIVITY OPTIONS

- Long-range Bluetooth® Smart Ready wireless technology, v5.0 +EDR, Class 1.5, BLE support
- Wi-Fi® 802.11 a/b/g/n/ac, 2.4 GHz and 5 GHz
- 4G LTE

CAMERA (GEO MODELS)

- Rear: 8 MP with LED illumination
- Front: 2 MP
- Juniper Geotagging™: embed photo with date, time, and GNSS position

GPS/GNSS (GEO MODELS)

- 2 to 5 meter typical accuracy
- uBlox NEO-M8N GNSS receiver and integrated antenna
- Integrated real-time SBAS receiver (WAAS, EGNOS, etc.)
- 72 GNSS tracking channels
- Optional: uBlox NEO-M8T w/post-processing capability and external GNSS antenna pass-through connection for sub-meter accuracy

BARCODE 1D/2D IMAGER (BARCODE MODELS)

- Optional built-in barcode imager and decoder
- Symbologies: all common 1D and 2D (PDF 417, MicroPDF417, Composite, RSS, TLC-39, Data matrix, QR code, Micro QR code, Aztec, MaxiCode, Postal codes, etc.)
- Programmable trigger buttons
- Visible aiming bullseye with low-light illumination
- Barcode Connector™ Utility, wedge and configuration, SDK support available

UHF RFID (RFID MODELS)

- Optional built-in UHF RFID module and internal antenna
- Region-specific frequency configurations (859–873 MHz & 915–930 MHz)
- EPCglobal Gen 2 (ISO 18000-6C) protocol support
- Wide output range (0 dBm to +27 dBm)

OTHER FEATURES

- Ambient light sensor
- Compass
- Accelerometer
- Gyroscope
- TPM (Trusted Platform Module) v2.0

CERTIFICATIONS AND STANDARDS

- FCC Class B
- CE Marking (applicable EMC, R&TTE, and LVD directives)
- Industry Canada
- EN62368 Safety
- RoHS 2 Compliant
- Optional Class I, II, & III, Division 2



STANDARD ACCESSORIES

- Standard removable battery
- AC wall charger with international plug kit
- Capacitive small-tip stylus w/tether
- Quick Start Guide
- Hand strap
- Connector port dust cover
- 2-year warranty

CUSTOMIZATION

- Available upon request